



PENTARCH
FORESTRY®

metallon XL™
ENGINEERED FLOORING

metallon XL™

Pentarch Forestry's metallon XL™ engineered flooring envelopes the earthy beauty of timber flooring and contemporary aesthetics of precious metals, creating a synergy that is truly indulgent.

Engineered Flooring

With click lock installation, metallon XL™ seamlessly integrates into your space. Pre-finishing minimises the extra work required and allows for versatility with its ability to be sanded back to reveal a more natural finish.

- Available in Blackbutt with stained finishes
- No mess and fumes from sanding and finishing
- Low sheen high quality European UV cured acrylic lacquer
- Minimum 100gsm film build, for better wearability
- Easy installation over multiple surface types
- Features the UNICLIC® locking system on all four sides
- Unique colour and grain variations to suit any requirements
- Graded to AS 2796.2 Standard and better - PEFC Certified

Specifications

Size	186mm x 14mm
Board Lengths	up to 2200mm*
Film Build	Min 100gsm
Wear Layer (Nominal)	3mm
Grade	Standard and Better
Species	Blackbutt (Janka 8.9)
Edge	Micro bevelled long edges
Finish	Wire brushed textured surface

Colours



Aztec White




Sterling



Quicksilver



Copper#



Tungsten

*Up to 6 short boards per box #Fumed which allows the copper tones to be infused into the Blackbutt veneer ^ For more information, visit pentarchforestry.com.au/ecoCORK

Installation

metallon XL™ engineered flooring can be glued or "floated" over any level subfloor such as a concrete slab, particleboard or plywood sheeting or over old timber floors or tiles. Underlays assists with floor levelling, cushioning and acoustic properties. Pentarch Forestry has a variety of quality underlays, such as ecoCork Insulation Acoustic Underlay^, that can be installed with timber flooring to provide a range of quality flooring solutions for any venue.



Tungsten



Copper





Sterling

metallon XL™



Care & Maintenance

With regular care and maintenance, you can enjoy a lifetime of beauty with your metallon XL™ floor.

- For daily cleaning, use dry methods such as vacuuming and sweeping. To remove stubborn dirt, use a well-rung mop and a pH neutral cleaner. Do not clean timber floors with a steam mop.
- Place doormats at entrances, non-slip rugs in high-wear areas and protective pads under furniture legs.
- Do not use any abrasive brushes, steel wool, soap detergents or ammonia based cleaners.
- Always take care when moving appliances and furniture by placing them on a sturdy mat to slide into position.



Responsible Wood™
RW/7-31-217



PEFC™
PEFC/21-31-217

Sustainably Grown. Australian Made.

Note: Variations within a timber species are normal, therefore photographs, samples and displays can only be indicative of colour and should not be used for final selection. It is normal for natural timber products to react to changes in atmospheric and environmental conditions such as humidity and temperature.

pentarchforestry.com.au
1800 818 317

©2025 PENTARCH FORESTRY PTY LTD (ABN 22 159 663 420). Pentarch Forestry and the Pentarch Forestry logo are trade marks or registered trade marks of PENTARCH FORESTRY PTY LIMITED or one of its subsidiaries. PEN_0388



PENTARCH
FORESTRY®